

FULL RACE	*50	57	63	*70	75	*80	85	FULL CARVE	50	57	63	70	75	80
Overall Length	1500	1570	1630	1700	1750	1800	1850	Overall Length	1500	1570	1630	1700	1750	1800
Running Length	1330	1400	1460	1530	1580	1630	1680	Running Length	1330	1400	1460	1530	1580	1630
Nose Length	120	120	120	120	120	120	120	Nose Length	120	120	120	120	120	120
Tail Length	50	50	50	50	50	50	50	Tail Length	50	50	50	50	50	50
Nose Width	250	251	260	251	245	252	250	Nose Width	250	251	260	251	245	252
Waist Width	190	190	203	199	190	203	202	Waist Width	190	190	203	199	190	203
Tail Width	230	231	240	228	222	227	229	Tail Width	230	231	240	228	222	227
Sidecut Radius	9450	10000	11800	15700	15300	19200	20300	Sidecut Radius	9450	10000	11800	15700	15300	19200
Setback	60	60	60	60	60	60	60	Setback	60	60	60	60	60	60
Stance Range	420-540	440-560	460-580	460-580	460-580	460-580	460-580	Stance Range	420-540	440-560	460-580	460-580	460-580	460-580
Insert Pattern	4x2	4x2	4x2	4x2	4x2	4x2	4x2	Insert Pattern	4x2	4x2	4x2	4x2	4x2	4x2
Suggested Settings								Suggested Settings						
Reference Stance	480	480	500	500	500	500	500	Reference Stance	480	500	500	500	500	500
Angles Front	45°-57°	45°-57°	45°-57°	45°-57°	45°-57°	45°-57°	45°-57°	Angles Front	45°-57°	45°-57°	45°-57°	45°-57°	45°-57°	45°-57°
Angles Back	43°-54°	43°-54°	43°-54°	43°-54°	43°-54°	43°-54°	43°-54°	Angles Back	43°-54°	43°-54°	43°-54°	43°-54°	43°-54°	43°-54°
Edge Tuning Base	0,5°-1°	0,5°-1°	0,5°-1°	0,5°-1°	0,5°-1°	0,5°-1°	0,5°-1°	Edge Tuning Base	0,5°-1°	0,5°-1°	0,5°-1°	0,5°-1°	0,5°-1°	0,5°-1°
Edge Tuning Side	87°-88°	87°-88°	87°-88°	87°-88°	87°-88°	87°-88°	87°-88°	Edge Tuning Side	87°-88°	87°-88°	87°-88°	87°-88°	87°-88°	87°-88°

*Full Race Titan length only

RACE JR	25	40	FORCE	55	60	60 FAT	65	65 FAT	FREE SOLO	52	57	62	67
Overall Length	1250	1400	Overall Length	1550	1600	1600	1650	1650	Overall Length	1520	1570	1620	1670
Running Length	1020	1150	Running Length	1330	1400	1380	1450	1450	Running Length	1121	1160	1300	1300
Nose Length	180	200	Nose Length	140	120	140	120	120	Nose Length	212	205	170	200
Tail Length	50	50	Tail Length	80	80	80	80	80	Tail Length	187	205	150	170
Nose Width	234	243	Nose Width	286	293	296	304	308	Nose Width	293	290	285	307
Waist Width	185	190	Waist Width	246	245	258	253	260	Waist Width	249	250	254	260
Tail Width	228	236	Tail Width	265	272	277	281	285	Tail Width	292	290	276	300
Sidecut Radius	6000	7300	Sidecut Radius	12800	13000	13500	14000	14500	Sidecut Radius	7900	8000	10000	10000
Setback	10	10	Setback	35	60	35	60	60	Setback	20	15	30	45
Stance Range	250-410	320-480	Stance Range	420-620	480-680	460-660	480-680	480-680	Stance Range	400-600	460-660	460-660	460-660
Insert Pattern	4x4	4x4	Insert Pattern	POW 4x2	POW 4x2	POW 4x2	POW 4x2	POW 4x2	Insert Pattern	POW 4x2	POW 4x2	POW 4x2	POW 4x2
Suggested Settings			Suggested Settings						Suggested Settings				
Reference Stance	330	400	Reference Stance	560	580	580	580	580	Reference Stance	540	560	560	560
Angles Front	40°-50°	40°-50°	Angles Front	15°-35°	15°-35°	15°-35°	15°-35°	15°-35°	Angles Front	15°-35°	15°-35°	15°-35°	15°-35°
Angles Back	35°-45°	35°-45°	Angles Back	5°-25°	5°-25°	5°-25°	5°-25°	5°-25°	Angles Back	5°-25°	5°-25°	5°-25°	5°-25°
Edge Tuning Base	0,5°-1°	0,5°-1°	Edge Tuning Base	1°-1,5°	1°-1,5°	1°-1,5°	1°-1,5°	1°-1,5°	Edge Tuning Base	1°-1,5°	1°-1,5°	1°-1,5°	1°-1,5°
Edge Tuning Side	87°-88°	87°-88°	Edge Tuning Side	88°	88°	88°	88°	88°	Edge Tuning Side	88°	88°	88°	88°

THE CULT	69	GRAND TRAVERSE	60	70	SHRED	35	45
Overall Length	1690	Overall Length	1600	1700	Overall Length	1350	1453
Running Length	1390	Running Length	1350	1450	Running Length	1040	1085
Nose Length	200	Nose Length	150	150	Nose Length	160	189
Tail Length	100	Tail Length	100	100	Tail Length	160	179
Nose Width	295	Nose Width	295	300	Nose Width	267	288
Waist Width	245	Waist Width	268	272	Waist Width	230	244
Tail Width	280	Tail Width	285	290	Tail Width	267	288
Sidecut Radius	11802	Sidecut Radius	12250	15126	Sidecut Radius	7500	7000
Setback	20	Setback	50	50	Setback	0	0
Stance Range	470-550	Stance Range	540-620	540-620	Stance Range	420-500	400-560
Insert Pattern	4x2	Insert Pattern	POW 4x2	POW 4x2	Insert Pattern	4x2	POW 4x2
Suggested Settings		Suggested Settings			Suggested Settings		
Reference Stance	510	Reference Stance	580	580	Reference Stance	460	500
Angles Front	30°-45°	Angles Front	15°-35°	15°-35°	Angles Front	15°-35°	15°-35°
Angles Back	25°-40°	Angles Back	5°-25°	5°-25°	Angles Back	5°-25°	5°-25°
Edge Tuning Base	1°-1,5°	Edge Tuning Base	1°-1,5°	1°-1,5°	Edge Tuning Base	1°-1,5°	1°-1,5°
Edge Tuning Side	88°	Edge Tuning Side	88°	88°	Edge Tuning Side	88°	88°

*POW inserts for 45 length



IMPORTANT FOR TITANAL BOARDS !

Special competition tune-up is necessary for all boards with Titanal Setup. The sidewalls in the nose area must be bevelled for better protection against stubby impacts. Warranty does not apply to delaminations due to stubby impacts. Check the instruction video on our website www.sgsnowboards.com or write to mail@sgsnowboards.com for more information.

all mountain sports Vertriebs GmbH

Untergaimberg 1 1 mobile: +43 664 12 12 521
 9905 Gaimberg www.sgsnowboards.com
 Tirol, Austria mail@sgsnowboards.com